

Research Paper



Evaluating the impacts of sewage disposal on groundwater composition in the peri-urban community: a case of Ikoto-Ijebu, Ogun State, Nigeria

A. Obafemi Solesi^{1*}, A. Sunday Abiodun², O. Olatunde Solaja³

^{1*}Department of Pharmacy Technician Programme, Ogun State Polytechnic of Health and Allied Sciences, Ilese-Ijebu, Nigeria.

^{2,3}Department of Environmental Health and Diseases Control, Ogun State Polytechnic of Health and Allied Sciences, Ilese-Ijebu, Nigeria.

Article Info

Article History:

Received: 26 December 2023

Revised: 06 March 2023

Accepted: 12 March 2023

Published: 08 May 2023

Keywords:

Acidity

Coliform

Electrical Conductivity

Groundwater

Temperature



ABSTRACT

Groundwater is an essential resource that requires sufficient protection from human-induced pollution sources, assessments of water quality is an essential tool for water resources management strategies. The physicochemical parameters measured were Hydrogen ion concentration (pH), Temperatures (°C), and electrical conductivity (EC), total bacteria and faecal coliform counts (Tb/fcc) were determined using the membrane-filtration method; pH values was measure using a pH meter (Hach), the pH meter sensitivity was determined using buffers with a pH of 4.0 and pH of 9.0 and electrical conductivity values were taken, the TDS, total dissolved solids, measured using a meter; the SO₄²⁻, Fe²⁺ and NO₃⁻ were determined using Hach DR/2000 spectrophotometer. The water sampled temperatures range between 25.80 °C and 27.90 °C and arithmetic mean of 25.85 °C. The pH values of sampled wells and boreholes were in the acceptable pH range of 6.5 – 8.5, electrical conductivity values measured from the samples ranged from 94 µS per cm to 1418 µS per cm, having an arithmetic average of 370 µS/ cm; it is just one well that exceeded the permissible limit of 1000 µS per cm. The Total Dissolved Solids values ranged from 73 mg per Litre to 528 mg per Litre, an arithmetic average of 370 mg per Litre. The maximum value of 528 mg per Litre from zone B exceeded the acceptable limit of 500 mg per Litre. The concentrations are from 5 to 27×10 cfu / mL for total coliform counts and 0 to 12×10 cfu / mL for *E. coli*. 77.2% of the samples fall within BOD values >3 mg per Litre, and 32.8% had BOD > 5 mg per Litre, signifying biogenic pollution and a possible seepage of mildly treated wastewater from sewage tanks near the wells. BOD and the bacteriological studies, for assessing biogenic pollution in water, indicated water samples are contaminated with wastewater.

Corresponding Author:

A. Obafemi Solesi

Department of Pharmacy Technician Programme, Ogun State Polytechnic of Health and Allied Sciences, Ilese-Ijebu, Nigeria.

Email: solesi.obafemi@gmail.com

Copyright © 2023 The Author(s). This is an open access article distributed under the Creative Commons Attribution License, (<http://creativecommons.org/licenses/by/4.0/>) which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

1. INTRODUCTION

Groundwater is an essential resource that requires sufficient protection from human-induced pollution sources. Human actions and resultant climate change have affected the standard quality of both surface and underground water [1], [2], especially from newly uptake pollutants through agricultural processes, nitrate, pesticides, other heavy metals and organic products, and volatile organic carbons; are a potential danger to human health and groundwater sustainability [3], [4], [5], [6], [7].

Among other water sources, groundwater is a source of fresh water and a dependable means of water provision in Nigerian communities and was considered less contaminated by pollution to surface running waters [8]; earth's surface groundwater quality relies on other factors: - the quality of inflow water, precipitation, rural-urban dumpsites and landfill systems and significantly, the form of sewerage systems adopted in the population [9]. In Nigeria, municipal's municipal wastewater treatment systems are not adopted estates and landlords have their installed domestic wastewater platforms.

Water pollution has been a global problem, and groundwater pollution results from industrial effluents cum domestic sewage into watercourses [10]; the results; on health and environmental impacts consequential to water-related disease and the assessments of water quality is an essential tool for water resources management strategies [11]; some findings evaluated and recorded the consequences of drainage systems as adopted in our villages and cities on groundwater quality; hence, we aimed to assess the impacts of sewage disposal on groundwater in Ikoto, Ogun State, Nigeria.

2. MATERIALS AND METHODS

2.1 Sample Collection

Sample- surveyed using direct observation, water sampling and analysis of the water samples; twenty-one water wells and boreholes were marked using the global positioning system locations; three replicates of water samples were fetched from each borehole and well into 1 Liter plastic bottles; First twenty-one sample were used for the cation determination, another set of twenty-one samples for the anion determination, and the last set for biological analysis; the Physicochemical parameters measured were Hydrogen ion concentration (pH), Temperatures (°C), and electrical conductivity (EC), total bacteria and faecal coliform counts (Tb/fcc) were determined using the membrane-filtration method; pH values was measure using a pH meter (Hach), the pH meter sensitivity was determined using buffers with a pH of 4.0 and pH of 9.0 and electrical conductivity values were taken, the TDS, total dissolved solids, measured using a meter; the SO_4^{2-} , Fe^{2+} and NO_3^- were determined using Hach DR/2000 spectrophotometer following [12].

Twenty-one (21) sampling locations (seven from each zone within the community) had hand-dug wells and boreholes less than or equal to 15 m from sewage tank units selected randomly.

Samples were collected; in February 2019 aseptic techniques; and quality control measures taken during analysis.

The water samples from the two primary sources, wells and boreholes, were kept in protected bottles with ice packs to maintain cooling while transporting them to the laboratory for further analysis;

for metal analysis, sample bottles added with 2 mL of HNO_3 (conc.); for microbial analysis, water samples were in sterilized bottles.

2.2 Water Quality Parameters

Groundwater parameters evaluated include hydrogen ion concentration (pH), Temperature ($^{\circ}\text{C}$), Electrical Conductivity (EC), Total dissolved solids (TDS), Ca^{2+} , Mg^{2+} , Na^{+} , K^{+} , and Cl^{-} , NO_3^{2-} , SO_4^{2-} , PO_4^{3-} , and biochemical oxygen demand (BOD), HI98129 electrode calibrated with buffers of pH 4.0 and 9.0 used to measure pH, Temperature, electrical conductivity, and total dissolved solids (TDS) on site.

Spectrophotometric analysis of the samples was to determine Ca^{2+} , Mg^{2+} , Na^{+} and K^{+} using PinAAcle 500 Flame Atomic Absorption Spectrometer and Hach DR/2000 spectrophotometer for SO_4^{2-} , PO_4^{3-} , and NO_3^{2-} ; Escherichia coli and Total Coliform Count determined using the membrane filtration method and Azide modification of the Winkler method for biological oxygen demand.

Nigerian Standard for Drinking Water and World Health Organization drinking water quality guidelines were the two standards used to compare the water quality parameters results from the study area.

3. RESULTS AND DISCUSSION

The physical parameters with cations being Na^{+} , K^{+} , Ca^{2+} and Mg^{2+} , and anions Cl^{-} , NO_3^{-} , SO_4^{2-} and PO_4^{3-} in groundwater for the different zones in the community as shown in Table 1.

The water sampled temperatures range between 25.80°C and 27.90°C and arithmetic mean of 25.85°C . A rise in water temperature negatively influences water quality, encouraging microbial population and affecting taste, odour, colour and corrosion of metals [13]. The pH values of sampled wells and boreholes were in the acceptable pH range of 6.5 – 8.5, with a pH of less than 6.32 [14], [15]. A slightly acidic pH of one of the samples Area may be the contribution of human activities and sulphide oxidation in host rocks minerals [16]. The pH mean- value of the samples was 6.89. pH measures hydrogen ion concentration or basicity of H_2O and is for assessing the potability of water. Metal pipes and plumbing systems usually corroded with alkaline water, and water having a $\text{pH} < 6.5$ is contamination with microorganisms of gastrointestinal tracts importance leading to diarrhoea [17].

The presence of free ions such as Ca^{2+} , Mg^{2+} and Cl^{-} in water is a potential that the water can transmit electrical conductivity (EC). Electrical conductivity values measured from the samples ranged from $94\ \mu\text{S}$ per cm to $1418\ \mu\text{S}$ per cm, having an arithmetic average of $370\ \mu\text{S}/\text{cm}$; it is just one well that exceeded the permissible limit of $1000\ \mu\text{S}$ per cm. The electrical conductivity has varied values indicating different levels of inorganic minerals built up from human engagements. Although high electrical conductivity values in H_2O content do not pose a danger to human health, except for a noticeable mineral-salt taste in water consumed and exponential production costs for industrial utilization, also, EC values more than $700\ \mu\text{S}$ per cm are not for irrigation of farms due to formation of alkaline soils [18]. Groundwater samples from zone A and B have higher EC than groundwater samples from C in the same communities.

The Total Dissolved Solids values ranged from 73 mg per Litre to 528 mg per Litre, an arithmetic average of 370 mg per Litre. The maximum value of 528 mg per Litre from zone B exceeded the acceptable limit of 500 mg per Litre as prescribed by the NSDWQ [15].

The biological oxygen demand (BOD) is also an important parameter that measures water quality, indicating the microorganism decomposition of biogenic substances in water. Waters with biological oxygen demand values of 1 and 2 mg per Litre means clean water; 3 to 5 mg per Litre the water is of questionable quality but biological oxygen demand exceeding 5 mg per Litre confirmed biogenic pollution origins [19]. In this study, BOD ranged from 0.09 mg per Litre - 10.6 mg per Litre, with an arithmetic average of 4.9 mg per Litre. 77.2% of the samples fall within BOD values >3 mg per Litre, and 32.8% had BOD > 5 mg per Litre, signifying biogenic pollution and a possible seepage of mildly treated wastewater from sewage tanks near the wells.

The cations are in increasing sequence with $\text{Ca}^{2+} > \text{Mg}^{2+} > \text{Na}^{+} > \text{K}^{+}$. The calcium concentrations in the samples range from 36.05 mg per Litre to 163.60 mg per Litre, with an arithmetic average of 32.1 mg

per Litre for the study area. Magnesium ions ranged between 2.35 mg per Litre to 52.3 mg per Litre, with a mean value of 23.03 mg per Litre.

Over 58% of the samples had $\text{Ca}^{2+} > 75$ mg per Litre as prescribed by the WHO and NSDWQ for drinking water. Likewise, 61% of groundwater sampled had Mg^{2+} exceeding 20 mg L⁻¹ as recommended by the World Health Organization and Nigerian Standard for Drinking Water. Water samples with both Calcium and Magnesium can be associated with the dissolution of sedimentary rocks; examples are limestone and shale. And they cause hardness in water [20]. Inadequate intake of calcium and magnesium can result in adverse health status, being essential minerals. The high proportion of calcium- ions and magnesium ions in hard water is not a health risk factor except for marginal calcium and magnesium intake [21].

The concentrations of Na^+ ranged between 7.75 mg per Litre - 48.15 mg per Litre, having Na^+ conc with an acceptable limit of 200 mg per Litre as recommended by the World Health Organization and Nigerian Standard for Drinking Water. The conc. of Potassium in the sample is between 1 mg Litre to 31.05 mg Litre. Na^+ in the groundwater is from the resident rock dissociation, and K^+ is also from resident rock release and as leachate of agricultural residues [18].

The two dominant anions were Cl^- and SO_4^{2-} in wells and boreholes studied. The rate of the increasing sequence is $\text{Cl}^- > \text{SO}_4^{2-} > \text{NO}_3^- > \text{PO}_4^{3-}$ as shown in Table 1; the presence of Cl^- was a good indicator of wastewater effluent discharge to bodies of water. The amount is always high when close to sewage or waste outlets and irrigation drains [19]. Two hundred and fifty milligrams per litre is the maximum limit allowed for drinking water. The chloride content in wells and boreholes water sampled was in the mean of 77.70 mg per Litre and ranged between 23.21 mg per Litre to 224 mg per Litre. The chlorine concentrations are within the allowable limit of 250 mg Litre for potable water. The conc. of SO_4^{2-} in samples was in a mean of 33.48 mg per Litre ranging between 16.48 mg Litre - 62.17 mg per Litre and in the limit of 100 mg per Litre as allowed by the authorities.

Table 1. Physicochemical Analysis of Water Samples

Area	Range	Temp (°C)	pH	TDS (mg/L)	BOD (mg/L)	EC (μS/cm)	K^+ (mg/L)	Ca^{2+} (mg/L)	Mg^{2+} (mg/L)	Na^+ (mg/L)
A	Min	26.50	6.12	121.0	0.09	485	2.43	84.00	37.18	10.00
	Mean	26.90	6.89	274.5	1.67	861	16.74	97.50	44.91	24.50
	Max	27.30	7.65	428.0	3.24	752	31.05	111.00	52.63	29.00
B	Min	26.45	6.32	46.0	5.23	94	4.00	36.05	2.35	7.75
	Mean	26.79	7.05	287.0	5.99	756	14.00	94.18	23.03	27.95
	Max	27.12	7.78	528.0	6.74	1418	24.00	152.30	43.70	48.15
C	Min	25.80	7.33	73.0	4.76	167	3.00	43.02	15.50	14.09
	Mean	25.852	7.60	174.0	7.68	370	9.50	103.31	30.95	25.12
	Max	7.90*	7.86	275.0	10.60	572	16.00	163.60	46.40	36.15

Table 1 (continued). Anion Concentrations of Water Samples

Area	Range	Cl^- (mg/L)	NO_3^- (mg/L)	SO_4^{2-} (mg/L)	PO_4^{3-} (mg/L)
------	-------	----------------------	------------------------	---------------------------	---------------------------

A	Min	54.05	7.43	27.10	0.30
	Mean	80.76	10.76	44.21	0.54
	Max	107.46	14.12	61.31	0.78
B	Min	42.06	6.13	28.33	63.32*
	Mean	77.70	10.13	45.25	32.07*
	Max	112.87	14.24	62.17	0.81
C	Min	23.21	5.70	16.48	0.23
	Mean	123.60	11.67	32.01	0.46
	Max	224.00	17.64	47.54	0.69

Groundwater should not contain any microorganisms except contamination through some vectors in the soil. Any trace of gastrointestinal bacteria in the groundwater reflects the water is in contact with human excrete or animal faeces; if detected in groundwater, this strongly indicates sewage contamination [22]. The bacteriological evaluation of the samples using *Escherichia coli* counts. The bacteriological analysis of samples showed a significant concentration of *E. coli* shown in Table 2. The concentrations are from 5 to 27×10 cfu / mL for total coliform counts and 0 to 12×10 cfu / mL for *E. coli*. These values are beyond the World Health Organization and Nigerian Standards for drinking water. Eighty per cent of water samples contained *E. coli* maximum being 27×10 CFU/ mL; thirty-five per cent of the sampled water has *E. coli* shown in Table 2. These results confirm that groundwater in the studied area was contaminated by sewage.

Table 2. Bacteriological Analysis ($\times 10$ cfu mL⁻¹) of Groundwater in the Study Area

Area	Range	TCC	E. coli
A	Min	8	0
	Mean	14	4
	Max	20	4
B	Min	5	3
	Mean	12	6
	Max	18	9
C	Min	11	5
	Mean	19	9
	Max	27	12

4. CONCLUSION

In a peri-urban community such as ikoto - ijebu, being the study area, groundwater is predominantly source of potable water. Evaluating groundwater in the study area is considered as socio-environmental safety study. The water quality parameters were mostly within permissible limits. Although, BOD and the bacteriological studies, for assessing biogenic pollution in water, indicated water samples are contaminated with wastewater.

Acknowledgments

The authors wish to thank all the researchers whose published works have been cited in this study.

Funding Information

This research has received no external funding.

Authors Contributions Statement

Name of Author	C	M	So	Va	Fo	I	R	D	O	E	Vi	Su	P	Fu
A. Obafemi Soles	✓	✓			✓	✓		✓	✓		✓		✓	

A. Sunday Abiodun	✓			✓		✓	✓			✓		✓	
O. Olatunde Solaja		✓	✓		✓		✓	✓		✓			✓

C : Conceptualization

M : Methodology

So : Software

Va : Validation

Fo : Formal analysis

I : Investigation

R : Resources

D : Data Curation

O : Writing - Original Draft

E : Writing - Review & Editing

Vi : Visualization

Su : Supervision

P : Project administration

Fu : Funding acquisition

Conflict of Interest Statement

No conflict of interest.

Informed Consent

Not Applicable.

Ethical Approval

Not Applicable.

Data Availability

This study draws on publicly available data. No new datasets were created.


REFERENCES



- [1] M. B. Arain, T. G. Kazi, M. K. Jamali, N. Jalbani, H. I. Afridi, and A. Shah, "Total dissolved and bioavailable elements in water and sediment samples and their accumulation in *Oreochromis mossambicus* of polluted Manchar Lake," *Chemosphere*, vol. 70, no. 10, pp. 1845–1856, 2008. doi.org/10.1016/j.chemosphere.2007.08.005
- [2] H. Bu, X. Tan, S. Li, and Q. Zhang, "Temporal and spatial variations of water quality in the Jinshui River of the South Qinling Mts., China," *Ecotoxicol. Environ. Saf.*, vol. 73, no. 5, pp. 907–913, 2010. doi.org/10.1016/j.ecoenv.2009.11.007
- [3] K. Kumazawa, "Nitrogen fertilization and nitrate pollution in groundwater in Japan: Present status and measures for sustainable agriculture," *Nutr. Cycl. Agroecosyst.*, vol. 63, no. 2–3, pp. 129–137, 2002. doi.org/10.1023/A:1021198721003
- [4] M. Jalali and Z. Kolahchi, "Groundwater quality in an irrigated, agricultural area of northern Malayer, western Iran," *Nutr. Cycl. Agroecosyst.*, vol. 80, no. 1, pp. 95–105, 2008. doi.org/10.1007/s10705-007-9123-5
- [5] I. Balogun and O. Adegun, "Seasonal evaluation of groundwater quality around Igando dumpsites in Lagos metropolis using correlation and regression analysis," *J. Appl. Sci. Environ. Manage.*, vol. 17, no. 2, pp. 329–333, 2013. doi.org/10.4314/jasem.v17i2.16
- [6] L. Salami and A. A. Susu, "Leachate characterization and assessment of groundwater quality: A case of Soluos dumpsite, Lagos, Nigeria," *Greener J. Sci. Eng. Technol. Res.*, vol. 3, no. 2, pp. 42–61, 2013. doi.org/10.15580/GJSETR.2013.2.112712298
- [7] M. I. Ocheri, L. A. Odoma, and N. D. Umar, "Groundwater quality in Nigerian urban areas: A review," *Global J. Sci. Front. Res. H Environ. Earth Sci.*, vol. 14, pp. 35–45, 2014.
- [8] C. N. Egbinola and A. C. Amanambu, "Groundwater contamination in Ibadan, South-West Nigeria," *SpringerPlus*, vol. 3, Art. no. 448, 2014. doi.org/10.1186/2193-1801-3-448
- [9] O. F. Kayode, C. Luethi, and E. R. Rene, "Management recommendations for improving decentralized wastewater treatment by the food and beverage industries in Nigeria," *Environments*, vol. 5, no. 3, Art. no. 41, 2018. doi.org/10.3390/environments5030041
- [10] R. A. Mashiatullah, M. Qureshi, A. Niaz, T. Javed, and A. Nisar, "Biological quality of ground water in Rawalpindi/Islamabad," *Environ. Monit.*, vol. 5, pp. 13–18, 2005.

- [11] F. Zhou, G. H. Huang, H. Guo, W. Zhang, and Z. Hao, "Spatio-temporal patterns and source apportionment of coastal water pollution in eastern Hong Kong," *Water Res.*, vol. 41, no. 15, pp. 3429–3439, 2007. doi.org/10.1016/j.watres.2007.04.022
- [12] A. Usman, B. C. E. Egboka, and A. O. Omali, "Seasonal variations in the physico-chemical and microbial characterization of groundwater in Lokoja, North Central Nigeria," *J. Basic Phys. Res.*, vol. 8, no. 2, pp. 117–134, 2018. doi.org/10.2139/ssrn.3325756
- [13] UNICEF, *Handbook on Water Quality*. New York, NY, USA: UNICEF, 2008, p. 179.
- [14] WHO, *Guidelines for Drinking-Water Quality*, 4th ed., incorporating the 1st addendum. Geneva, Switzerland: World Health Organization, 2017.
- [15] Standards Organisation of Nigeria, "Nigerian standard for drinking water quality (NSDWQ)," Abuja, Nigeria, 2015.
- [16] C. J. Whitfield, J. N. Phelan, J. Buckley, C. M. Clark, S. Guthrie, and J. A. Lynch, "Estimating base cation weathering rates in the USA: Challenges of uncertain soil mineralogy and specific surface area with applications of the PROFILE model," *Water Air Soil Pollut.*, vol. 229, Art. no. 61, 2018. doi.org/10.1007/s11270-018-3691-7
- [17] N. Rahmanian, S. H. B. Ali, M. Homayoonfard, N. J. Ali, M. Rehan, Y. Sadeh, and A. S. Nizami, "Analysis of physiochemical parameters to evaluate the drinking water quality in the State of Perak, Malaysia," *J. Chem.*, vol. 2015, Art. no. 716125, 2015. doi.org/10.1155/2015/716125
- [18] T. Sheikhy Narany, M. F. Ramli, A. Z. Aris, W. N. A. Sulaiman, H. Juahir, and K. Fakharian, "Identification of the hydrogeochemical processes in groundwater using classic integrated geochemical methods and geostatistical techniques, in Amol-Babol Plain, Iran," *Sci. World J.*, vol. 2014, Art. no. 419058, 2014. doi.org/10.1155/2014/419058
- [19] Bureau of Indian Standards, "Indian standard drinking water—Specification (Second Revision)," IS 10500, 2012.
- [20] S. Saha, A. H. Reza, and M. K. Roy, "Hydrochemical evaluation of groundwater quality of the Tista floodplain, Rangpur, Bangladesh," *Appl. Water Sci.*, vol. 9, no. 8, Art. no. 198, 2019. doi.org/10.1007/s13201-019-1085-7
- [21] P. Sengupta, "Potential health impacts of hard water," *Int. J. Prev. Med.*, vol. 4, no. 8, pp. 866–875, 2013.
- [22] N. Yang, Y. Li, L. Wang, L. Wang, and L. Niu, "Hydrodynamic conditions influence bacterial growth and phenol biodegradation of strains with different morphology and motility," *Water Air Soil Pollut.*, vol. 229, Art. no. 93, 2018. doi.org/10.1007/s11270-018-3695-3

How to Cite: A. Obafemi Soles, A. Sunday Abiodun, O. Olatunde Solaja. (2023). Evaluating the impacts of sewage disposal on groundwater composition in the peri-urban community: a case of Ikoto-Ijebu, Ogun State, Nigeria. *Journal of Environmental Impact and Management Policy (JEIMP)*, 3(1), 105–112. <https://doi.org/10.55529/jeimp.33.15.22>

BIOGRAPHIES OF AUTHORS

	A. Obafemi Soles, is a researcher and academic affiliated with the Department of Pharmacy Technician Programme, Ogun State Polytechnic of Health and Allied Sciences, Ilese-Ijebu, Nigeria. His research interests include pharmaceutical sciences, public health, environmental health, water quality, infectious diseases, and community health. He has contributed to research on groundwater quality, microbial contamination, malaria, and other health-related topics, with publications addressing important public health and environmental concerns in Nigeria. Email: solesi.obafemi@gmail.com
---	--

	A. Sunday Abiodun, is an academic and researcher in the Department of Environmental Health and Diseases Control at Ogun State Polytechnic of Health and Allied Sciences, Ilese-Ijebu, Nigeria. His research interests focus on environmental health, public health, disease prevention, environmental pollution, water quality, and community health. He has participated in research examining environmental contaminants, infectious diseases, sanitation, and health risks associated with environmental conditions. Email: abbeyabbey2011@yahoo.com
	O. Olatunde Solaja, is an academic and researcher in the Department of Environmental Health and Diseases Control, Ogun State Polytechnic of Health and Allied Sciences, Ilese-Ijebu, Nigeria. His research interests include environmental health, disease control, public health, environmental pollution, sanitation, and community health. His research contributions include studies examining environmental hazards, waste disposal, water quality, and health-related risks affecting communities in Ogun State, Nigeria. Email: tolaja2004@yahoo.com.hk